



SurMountor



SUR-S2835FW60-24V FLEXIBLE STRIP introduction

Product specification

Lister: Lxlan

Assessor: 

Approver: 

Features:


- Available in 24V DC maximum.
- Very bright & low power consumption.
- Operating temperature: -20~50°C.
- Long life span LED lights, more than 50,000 hours+.
- This model is specially designed for lighting box and can make 3D shape.
- Non-waterproof, IP20.

Applications:

Ideal for sign letters and channel letters, concealed lights, room lighting, equipment.




Assembly drawing

Top View




Section



S2835, 60LED/meter								
Part Number	Size	Color	Cut every (LEDS)	LED Qty/M	Lumen/M	Voltage	Power/m	Packing/m
SUR-S2835FWW60-24V	L5000*W6*H1.5	WW 	6	60	800	24V	10W	5 Meters/reel
SUR-S2835FNW60-24V		NW 			850			
SUR-S2835FCW60-24V		CW 			900			

Radiation diagram




Relative luminous intensity Iv %

LED Light distribution




Color Spectrum (CRI90)



How to connect flexible strip

Below shows you how to connect the flexible strip to power supplies.



Package:



1 reel/bag



25 bags/Inner Box

Inner box
size:25x26x31cm



50 Bags/Outer Box





Outer box
size:34x52x27cm




Package: 5 meter strip in one reel, one reel in one anti-static bag, 25 bags put into one inner box, 2 inner box put into one carton.

! Cautions:

When install the led strip, please note the installation technique. The led strip can be bent, but not distorted, as shown below:



Distortion(Wrong)



Bend (Right)