




# SurMountor



**SUR-2835FW120-12V**

FLEXIBLE STRIP introduction

Product specification

Lister: Lxlan

Assessor: 

Approver: 

## Features:

- Available in 12V DC maximum.
- CRI90 LED Strip.
- Very bright & low power consumption.
- Operating temperature: -20~50°C.
- Long life span LED lights, more than 50,000 hours+.
- Adhesive back, peel & stick!
- Non-waterproof, IP20.




## Applications:

Ideal for sign letters and channel letters, concealed lights, room lighting, equipment.

## Assembly drawing


### Top View




### Section



SMD2835,120LED/meter								
Part Number	Size	Color	Cut every (LEDS)	LED Qty/M	Lumen/M	Voltage	Power/m	Packing/m
SUR-2835FWW120-12V	L5000*W10*H3 or L5000*W12*H3	WW <input type="checkbox"/>	3	120	1180	12V	14.4W	5 Meters/reel
SUR-2835FNW120-12V		NW <input type="checkbox"/>			1330			
SUR-2835FCW120-12V		CW <input type="checkbox"/>			1480			






for: white LED

## How to connect flexible strip

Below shows you how to connect the flexible strip to power supplies.



## Package:



1 reel/bag



25 bags/Inner Box

Inner box  
size:25x26x31cm



50 Bags/Outer Box





Outer box  
size:34x52x27cm




Package: 5 meter strip in one reel, one reel in one anti-static bag, 25 bags put into one carton, 2 inner box put into 1 carton.

**! Cautions:**

When install the led strip, please note the installation technique. The led strip can be bent, but not distorted, as shown below:



**Distortion(Wrong)**



**Bend (Right)**